

# TL43-80HF 135 V R-Series Telescopic Handler

## Telescopic Specifications

### Performance

Rated capacity	4300 kg
Capacity (at max. height on tyres)	1800 kg
Capacity at max. reach	1600 kg
Lifting height	7505.0 mm
Tilt Breakout force	7000 daN
Drawbar pull	7200 daN
Max. reach	4022.0 mm

### Cycle times

Boom raising	6.5 s
Boom lowering	5.0 s
Boom extension	5.0 s
Boom retraction	4.5 s
Crowding	2.3 s
Dumping	2.0 s

### Weights

Unladen weight (24" tyres)	7985 kg
----------------------------	---------

### Engine

Make / Model	Bobcat D34
Fuel	DIESEL
Rated power (ISO 14396)	101.0 kW
Rated speed	2400.0 RPM
Maximum torque at 1400 rpm	500.0 Nm
Number of cylinders	4.0
Displacement	3.41 L

### Hydraulic system

Pump type	LS piston pump with electric displacement limiter
Pump capacity	190.00 L/min
Relief valve pressure setting	255.00 bar
Control valve type	Close center with flow sharing & flow compensators technology

### Drive system

Transmission	Hydrostatic with electronic regulation
Main Drive	Hydrostatic motor + 2 speed gearbox

### Traction

Standard Tyres	400/80-24 / 20PR TM R4
Low range - turtle mode (24" / 20")	6
Low range - rabbit mode (24" / 20")	11
High range - turtle mode (24" / 20")	16
High range - rabbit mode (24" / 20")	30
Low range - turtle mode (24" / 20") - (Option high speed)	6
Low range - rabbit mode (24" / 20") - (Option high speed)	12
High range - turtle mode (24" / 20") - (Option high speed)	18
High range - rabbit mode (24" / 20") - (Option high speed)	40

### Brakes

Engine Braking	Hydrostatic
Parking and Emergency brake	Passive brake
Service Brake	Oil immersed discs

### Steering

Steering Mode	2 wheel steering / 4 wheel steering / Crab-steering
---------------	---


### Fluid Capacities

Fuel tank	138.00 L
Adblue ® tank	28.80 L
Hydraulic tank	59.00 L
Hydraulic system	126.00 L

### Environmental

Operator noise level (LpA) (EN 12053)	73 dB(A)
Sound pressure level at the operator station 2014 /1322	73 dB(A)
Annexe XIII - 40kmh : doors closed (doors opened) (LpA)	
Level of acoustic power (LwA)	107 dB(A)
Whole body vibration (EN 13059)	1.20 ms <sup>-2</sup>

### Dimensions



Values marked with \* - 24" tyres

(A)	6180.0 mm	(L)	1352.0 mm
(B)	4975.0 mm	(M)	2870.0 mm
(C)	4585.0 mm	(N)	754.0 mm
(D*)	4256.0 mm	(O)	1013.0 mm
(E*)	2587.0 mm	(P)	1895.0 mm
(F*)	2457.0 mm	(Q)	2300.0 mm
(G)	152.0°	(R*)	4883.0 mm
(I*)	1770.0 mm	(S*)	3714.0 mm
(K)	346.0 mm	(U*)	1092.0 mm
(K*)	430.0 mm		

### Load Charts

Load Charts

